



STAR LINK IT

Wall Mounted Networking Cabinet Series

www.starlinkit.com		Model	Size	Description	Door Options
	WB-WM-A-6506	600*550*6U	▼ Double section welded or dis-assembled frame structure. ▼ Easy operation and maintaining at the back. ▼ 120mm fan option. ▼ Static loading 60kgs ▼ Turning angle of front/rear door is above 180 degrees/90 degrees. ▼ Flat packing has 1/3 volume. ▼ Removable side panels,side locks are optional,easily installed. ▼ SPCC cold rolled steel,1.0mm thickness for the body,1.5mm for 19" rails ▼ Standard allocations	■ Toughened glass door ■ Metal door ■ Vented door ■ Wave vented door	
	WB-WM-A-6509	600*550*9U			
	WB-WM-A-6512	600*550*12U			
	WB-WM-A-6515	600*550*15U			
	WB-WM-A-6518	600*550*18U			
	WB-WM-A-6522	600*550*22U			
	WB-WM-A-6527	600*550*27U			
	WB-WM-A-6622	600*600*22U			
	WB-WM-A-6627	600*600*27U			
	WB-WM-B-6406	600*450*6U	▼ Single section wall rack ▼ Flat packing saves 2/3 space. ▼ Easily mounting installation. ▼ Removable side panels,side locks are optional. ▼ Static loading 60kgs ▼ Cable entry on both of top cover and bottom panel. ▼ 120mm fan available. ▼ Turning angle of front door is over 180 degrees. ▼ SPCC cold rolled steel,1.0mm thickness for the body,1.5mm for 19" rails ▼ Standard allocations	■ Toughened glass door ■ Metal door ■ Vented door ■ Wave vented door	
	WB-WM-B-6409	600*450*9U			
	WB-WM-B-6412	600*450*12U			
	WB-WM-B-6415	600*450*15U			
	WB-WM-B-6418	600*450*18U			
	WB-WM-B-6422	600*450*22U			
	WB-WM-B-6427	600*450*27U			
	WB-WM-B-6615	600*600*15U			
	WB-WM-B-6618	600*600*18U			
	WB-WM-C-6406	600*450*6U	▼ SOHO smart cabinet is popular used at home and office,single section. ▼ Welded frame ,reliable structure. ▼ Adjustable feet and castors are optional. ▼ Removable side panels,side locks are optional. ▼ Turning angle of front door is over 180 degrees. ▼ Static loading 30kgs ▼ SPCC cold rolled steel,1.0mm thickness for the body,1.5mm for 19" rails ▼ Standard allocations	■ Toughened glass door ■ Metal door	
	WB-WM-C-6409	600*450*9U			
	WB-WM-C-6412	600*450*12U			
	WB-WM-C-6415	600*450*15U			
	WB-WM-C-6418	600*450*18U			
	WB-WM-C-6422	600*450*22U			
	WB-WM-C-6427	600*450*27U			
	WB-WM-C-6622	600*600*22U			
	WB-WM-C-6627	600*600*27U			
	WB-WM-D	300*350*4U	▲ 10" wall mounted cabinet ▲ Welded structure, stable, static loading: 30Kg. ▲ This is designed for SOHO; ▲ Front door full toughened glass with bolt lock ▲ Open angle for front door is over 180 degrees. ▲ 120mm size fan could be installed at top of cabinet. ▲ The side panels are welded,cable entry from top and bottom. ▲ IP Degree: IP20	■ Toughened glass door ■ Metal door	
		300*350*6U			
		300*350*9U			
		300*350*12U			
		300*350*15U			
		300*350*18U			
		300*350*22U			

	WB-WM-E-6406	600*450*6U	▲ Front door panel with special perforated design has handle lock or bolt lock for option ▲ 19 inch single section wall cabinet, quick and easy wall mounted. ▲ Reliable structure, static loading capacity: 60KG ▲ Front glass door with side doors which can be fixed lock, cable entry from top and bottom. ▲ Sizes from 4U to 22U as customer's requirements. ▲ The 19" profiles could be removable and adjustable ▲ Flat package is available, saving more space and freight	■ Toughened glass door ■ Metal door
	WB-WM-E-6409	600*450*9U		
	WB-WM-E-6412	600*450*12U		
	WB-WM-E-6415	600*450*15U		
	WB-WM-E-6418	600*450*18U		
	WB-WM-E-6422	600*450*22U		
	WB-WM-E-6427	600*450*27U		
	WB-WM-E-6615	600*600*15U		
	WB-WM-E-6618	600*600*18U		
	WB-WM-E-6622	600*600*22U		
	WB-WM-E-6627	600*600*27U		
	WB-WM-F-6406	600*450*6U	▲ Front perforated door with handle lock or bolt lock for option ▲ 19 inch single section wall cabinet, quick and easy wall mounted. ▲ Reliable structure, static loading capacity: 60KG ▲ Front vented door with side doors or welded side panels which can be fixed lock, cable entry from top and bottom. ▲ Sizes from 6U to 22U as customer's requirements. ▲ The 19" profiles could be removable and adjustable ▲ Flat package is available, saving more space and freight	■ Toughened glass door ■ Metal door
	WB-WM-F-6409	600*450*9U		
	WB-WM-F-6412	600*450*12U		
	WB-WM-F-6415	600*450*15U		
	WB-WM-F-6418	600*450*18U		
	WB-WM-F-6422	600*450*22U		
	WB-WM-F-6427	600*450*27U		
	WB-WM-F-6615	600*600*15U		
	WB-WM-F-6618	600*600*18U		
	WB-WM-F-6622	600*600*22U		
	WB-WM-F-6627	600*600*27U		
	WB-WM-G-6406	600*450*6U	▲ 19" mounting profiles are made of aluminum ▲ The front door is window type toughened glass door with bolt lock ▲ 19 inch single section wall cabinet, quick and easy wall mounted. ▲ Reliable structure, static loading capacity: 60KG ▲ The side panels are removable with lock or latches ▲ Cable entrance from top and bottom. ▲ The 19" profiles could be removable and adjustable ▲ Flat package is available, saving more space and freight	■ Toughened glass door ■ Metal door ■ Vented door ■ Wave vented door
	WB-WM-G-6409	600*450*9U		
	WB-WM-G-6412	600*450*12U		
	WB-WM-G-6415	600*450*15U		
	WB-WM-G-6418	600*450*18U		
	WB-WM-G-6422	600*450*22U		
	WB-WM-G-6618	600*600*18U		
	WB-WM-G-6622	600*600*22U		
	WB-WM-H	600*150*6U	▼ Welded metal frame, flush wall mounted type, reliable structure.	▼ Glass door
		600*150*9U	▼ With top and bottom cable entrances.	
		600*150*12U	▼ Front glass door with lock	
		600*150*15U	▼ Front glass door with around perforated holes for ventilation.	
		600*150*18U	▼ Static loading 20kgs	
		600*150*22U	▼ SPCC cold rolled steel, 0.8-1.0mm thickness for the body, 1.5mm for 19" rails	
			▼ Standard allocations	

More models can be added upon request

Notes: 1. both floor and wall cabinets can be assembled and flat packing; 2. both floor and wall cabinets can have different door options; 3. modifications and improvements: A: earth wire; B: expanse bolts for wall cabinet; C: all floor cabinet side panels have air circling area; D: all floor cabinet side panels have steady pins to avoid shape or gap; 4. accessories option: A: varies shelves and trays; B: varies cable managers; C: temperature sensor controller; D: beading decoration